



Purpose: How to change the WAN IP address

1. Go to Configuration/Ethernet Ports/WAN and select WAN.

Ethernet Ports & WAN Interface Configuration and Status

Current Interface Settings

Name Label	*Role	Cfg Mode	IP Address	Mask	Gateway	Link	Inet Access	Up / Down Link Speed (Kbps)
WAN	WAN	Static	67.130.149.164	255.255.255.224	67.130.149.190	Up	Available	15000 / 15000
Eth1	SUB	n/a	n/a	n/a	n/a	Down	n/a	n/a
Eth2	OOS	n/a	n/a	n/a	n/a	Down	n/a	n/a
Eth3	OOS	n/a	n/a	n/a	n/a	Down	n/a	n/a
Eth4	OOS	n/a	n/a	n/a	n/a	Down	n/a	n/a
Eth5	OOS	n/a	n/a	n/a	n/a	Down	n/a	n/a
LAGG0	OOS	n/a	n/a	n/a	n/a	Down	n/a	n/a
LAGG1	OOS	n/a	n/a	n/a	n/a	Down	n/a	n/a

[Show Summary](#)

Legend:

n/a

Non-applicable. Values are unnecessary for the chosen *Role*.

Unknown

Inet Access is *Unknown* if Port's *Link* is *Up* and *Interface Monitoring* is disabled.

*Role Configuration:

WAN

Wide Area Network

SUB

Subscriber Network

OOS

Out-of-Service



2. Modify the settings and click Save. **NOTE:** You will lose access to this management session once the changes have been submitted. You will need to open a new browser window to the new address to access the unit again.

Ethernet Ports & WAN Interface Configuration and Status

Current Interface Settings for port WAN

Label:

Role:

IPv6 Enabled:

IPv4 Configuration:

Cfg Mode:

IP Address: Gateway ARP Refresh Interval: seconds

Subnet Mask: Gateway:

DNS Domain: DNS Server 1:

DNS Server 2: DNS Server 3:

IPv6 Address Configuration:

IPv6 Address Cfg Mode: ⓘ

IPv6 Address:

IPv6 Prefix Length:

IPv6 Prefix Delegation for Subscriber Interfaces:

IPv6 Prefix:

IPv6 Prefix Length:

IPv6 DNS Server Configuration:

DNS IPv6 Server 1:

DNS IPv6 Server 2:

DNS IPv6 Server 3:

Uplink: Kbps Uplink speed to network

Downlink: Kbps Downlink speed to subscribers

WAN 802.1Q tagging: Enabled VLAN ID:

NAT IP Address Settings

Current Additional NAT IP Addresses:

Action	NAT IP
This interface does not have any NAT IP addresses configured for it.	

Additional NAT IP addresses: Enabled

NAT IP address:

0 additional NAT IP addresses are configured.